

OFFICE OF THE ILLINOIS STATE FIRE MARSHAL

Division of Technical Services

1035 Stevenson Drive Springfield, Illinois 62703-4259 (217)524-7605

Amended

FOR OFFICE USE ONLY

Facility # 2-043373
Permit # 01196-2006INS
Request Rec'd 08/14/2006
Amended Date 11/30/2006
Approval Date 8/15/2006 JC
Permit Expires 2/15/2007

Permit for INSTALLATION of Underground Storage Tank(s) and Piping for Petroleum and Hazardous Substances.

Permission to install underground storage tank(s) or piping is hereby granted. Such installation must be in complete accordance with acceptable materials as specified in the Federal Register, Part II Environmental Protection Agency, 40 CFR Parts 280 and 281, and also with all sections of 41 Illinois Administrative Code, Part 170. The contractor the permit was issued to or an employee of that contractor (this does not include a subcontractor) shall submit a required job schedule for installation of underground storage tank(s) to the Office of the State Fire Marshal, Division of Petroleum and Chemical Safety.

THIS PERMIT IS VALID FOR SIX MONTHS FROM THE APPRO	VAL DATE.
(1) OWNER OF TANKS - Corporation, partnership, or other business entity:	(2) <u>FACILITY</u> - name and address where tanks are located:
Local 150 Apprenticeship 19800 West Arsenal Rd. Wilmington, IL 60481	Local 150 Apprenticeship 19800 Wet Arsenal Road Wilmington, Will Co., IL
Contact: Jim Yasko	Contact: Jim Yasko
(3) INSTALLATION OF TANKS:	
(a) Number and size of tanks being installed: (TK # 1) - 10,	000 gallons
(b) Type of tanks: (TK # 1) - (Installing) Containment Solution	ons double wall fiberglass
(c) Type of piping: (TK # 1) - (Installing) Ameron Dualoy 30	000/LCX double wall fiberglass
(d) Product to be stored in each tank: (TK # 1) - Gasoline	
(e) Type of leak detection being used:	
<i>Tank:</i> (TK # 1) - (Installing) Veeder Root TLS 300c au interstitial tank sensor	atomatic tank gauge, (TK # 1) - (Installing) Veeder Root TLS 300c
Piping: (TK # 1) - (Installing) Veeder Root TLS300c in (TK # 1) - Interstitial sensor will be located at ta	nterstitial piping sump sensor, (TK # 1) - (Installing) European Suction ank sump only.
(f) Corrosion Protection being used: Tank: Piping: (TK # 1) - (Installing) Fiberglass	
, , , , , , , , , , , , , , , , , , ,	
(g) Spill containment devices:	
	
	ation has occurred, on the Notification for Underground Storage Tank Form for installation to the OSFM prior to the work being performed. Both form 20.
inches in diameter, installed in each new tank field of tanks larg water tight containment shall be installed under all dispensers a containments. All steel piping for vents, risers, and fills in con- coated. A positive shut off valve shall be installed on pressurize	of two manufactured slotted or perforated observation wells of at lease 4 ger than 1000 gallons and one well for tanks less than 1000 gallons. A and at submersible pumps. A hydrostatic test must be performed on all tact with the ground, backfill, or water shall be dielectrically wrapped or zed product lines, at the submersibles, or installed at the tank for all suction to grade level. All steel flex connectors in contact with ground, backfill of
(6) SPECIAL CONTINGENCIES:	
(7) PERSON, FIRM OR COMPANY PERFORMING WORK:	
	Contact Person:Phone:
	Contractor Registration # Exp.
Sincerely,	

Division File (Rev. - 1/98)