

business entity:

(1) **OWNER OF TANKS** - Corporation, partnership, or other

## OFFICE OF THE ILLINOIS STATE FIRE MARSHAL Division of Technical Services

1035 Stevenson Drive Springfield, Illinois 62703-4259 (217)524-7605

## FOR OFFICE USE ONLY

Facility # 4-013793
Permit # 00121-2006INS
Request Rec'd 01/04/2006
Amended Date
Approval Date 1/18/2006 MB
Permit Expires 7/18/2006

(2) FACILITY - name and address where tanks are located:

## Permit for INSTALLATION of Underground Storage Tank(s) and Piping for Petroleum and Hazardous Substances.

Permission to install underground storage tank(s) or piping is hereby granted. Such installation must be in complete accordance with acceptable materials as specified in the Federal Register, Part II Environmental Protection Agency, 40 CFR Parts 280 and 281, and also with all sections of 41 Illinois Administrative Code, Part 170. The contractor the permit was issued to or an employee of that contractor (this does not include a subcontractor) shall submit a required job schedule for installation of underground storage tank(s) to the Office of the State Fire Marshal, Division of Petroleum and Chemical Safety. **THIS PERMIT IS VALID FOR SIX MONTHS FROM THE APPROVAL DATE**.

Pride Oil, LLC 1505 W. Main	Mach 1 Food Shop 1701 Philo Road
Teutopolis, IL 62467	Urbana, Champaign Co., IL
Contact: Randy Meyer (217) 857-3163	Contact: Randy Meyer (217) 857-3163
3) <u>INSTALLATION OF TANKS:</u>	
(a) Number and size of tanks being installed: (TK # 11) - 15	,000 gallons, (TK # 12, 13, 14) - 8,000 gallons
(b) Type of tanks: (TK # 11, 12, 13, 14) - (Installing) ACT 10	00 single wall composite
(c) Type of piping: (TK # 11, 12, 13, 14) - (Installing) A.P.T.	Poly Tech P150SC double wall flexible
(d) Product to be stored in each tank: (TK # 11, 12) - Gasoli	ne, (TK # 13) - Diesel Fuel, (TK # 14) - E-85
(e) Type of leak detection being used:  Tank: (TK # 11, 12, 13, 14) - (Installing) Veeder Root  Piping: (TK # 11, 12, 13, 14) - (Installing) Veeder Root  (Installing) Veeder Root TLS350j electronic line	t TLS350j interstitial piping sump sensor, (TK # 11, 12, 13, 14) -
(f) Corrosion Protection being used:  Tank:	
<b>Piping:</b> (TK # 11, 12, 13, 14) - Existing non-corrosive to	lexible
(g) Spill containment devices:	
(h) Overfill prevention devices:	
	ntion has occurred, on the Notification for Underground Storage Tank Form for installation to the OSFM prior to the work being performed. Both forms 0.
inches in diameter, installed in each new tank field of tanks larg water tight containment shall be installed under all dispensers a containments. All steel piping for vents, risers, and fills in cont coated. A positive shut off valve shall be installed on pressuriz	If two manufactured slotted or perforated observation wells of at lease 4 per than 1000 gallons and one well for tanks less than 1000 gallons. A not at submersible pumps. A hydrostatic test must be performed on all act with the ground, backfill, or water shall be dielectrically wrapped or ed product lines, at the submersibles, or installed at the tank for all suction o grade level. All steel flex connectors in contact with ground, backfill or
6) SPECIAL CONTINGENCIES:	
(7) PERSON, FIRM OR COMPANY PERFORMING WORK:	
<del></del>	Contact Person:Phone:
	Contractor Registration # Exp.
Sincerely,  ———————————————————————————————————	

(Rev. - 1/98)