

OFFICE OF THE ILLINOIS STATE FIRE MARSHAL

Division of Petroleum and Chemical Safety

1035 Stevenson Drive Springfield, Illinois 62703-4259 (217)785-1020

FOR OFFICE USE ONLY

Facility # 6-045293
Permit # 00803-2013INS
Request Rec'd 08/14/2013
Amended Date
Approval Date 8/14/2013 DS
Permit Expires 2/14/2014

Permit for INSTALLATION of Underground Storage Tank(s) and Piping for Petroleum and Hazardous Substances.

Permission to install underground storage tank(s) or piping is hereby granted. Such installation must be in complete accordance with acceptable materials as specified in the Federal Register, Part II Environmental Protection Agency, 40 CFR Parts 280 and 281, and also with all sections of 41 Illinois Administrative Code, Parts 174, 175 and 176. The contractor the permit was issued to or an employee of that contractor (this does not include a subcontractor) shall submit a required job schedule for installation of underground storage tank(s) to the Office of the State Fire Marshal, Division of Petroleum and Chemical Safety. **THIS PERMIT IS VALID FOR SIX MONTHS FROM THE APPROVAL DATE**.

(1) OWNER OF TANKS - Corporation, partnership, or other	(2) <u>FACILITY</u> - name and address where tanks are located:
business entity:	
Sam's West Inc.	Sam's Club #4878
11206 Thompson Ave., Shaw Environmental Inc.	2799 Highway 159S,(SW corner of Center Grove Rd. & Troy
Lenexa, KS 66219	Rd.)
Contact: Char: Licensing (977) 920 5505	Glen Carbon, Madison Co., IL
Contact: Shaw Licensing (877) 829-5505	
	Contact: Shaw Licensing (877) 829-5505

(3) INSTALLATION OF TANKS:

- (a) Number and size of tanks being installed: (TK # 1, 2) 20,000 gallons, (TK # 3) 12,000 gallons, (TK # 4) 8,000 gallons
- (b) Type of tanks: (TK # 1, 2, 3, 4) (Installing) Fiberglass Double Wall XERXES
- (c) Type of piping: (TK # 1, 2, 3, 4) (Installing) Flexible Double Wall OPW Flexworks CP-15 non corrosive, (TK # 1, 2, 3, 4) (Installing) Chase Secondary Containment OPW AXP 40 secondary chase piping
- (d) Product to be stored in each tank: (TK # 1, 2, 3) Gasoline, (TK # 4) Diesel Fuel
- (e) Type of leak detection being used:

Tank: (TK # 1, 2, 3, 4) - (Installing) Interstitial Monitoring OPW EECO 2000, (TK # 1, 2, 3, 4) - (Installing) Automatic Tank Gauging OPW EECO 2000

Piping: (TK # 1, 2, 3) - (Installing) Mechanical Pressurized Line Leak Detection Red Jacket FX1V, (TK # 1, 2, 3, 4) - (Installing) Piping Sump Sensors Interstitial Monitoring OPW EECO 2000 in all submersible and all dispenser sumps, (TK # 4) - (Installing) Mechanical Pressurized Line Leak Detection Red Jacket FX1DV

(f) Corrosion Protection being used:

Tank: (TK # 1, 2, 3, 4) - (Installing) Fiberglass Non-Corrosive

Piping: (TK # 1, 2, 3, 4) - (Installing) Flexible Non-Corrosive

- (g) Spill containment devices, piping and dispenser containment devices: (TK # 1, 2, 3, 4) (Installing) Manhole Pre-manufactured OPW 1-2100 PEVR 5 gallon
- (h) Overfill prevention devices: (TK # 1, 2, 3, 4) (Installing) Overfill Drop Tube Valve OPW 71SO-410C overfill drop tube
- (4) The owner must notify this Office when completion of tank installation has occurred, on the Notification for Underground Storage Tank Form and the licensed contractor must submit the required job schedule for installation to the OSFM prior to the work being performed. Both forms can be obtained at www.sfm.illinois.gov or by calling (217)785-1020.
- (5) GENERAL REQUIREMENTS: There shall be a minimum of two manufactured slotted or perforated observation wells of at lease 4 inches in diameter, installed in each new tank field of tanks larger than 1000 gallons and one well for tanks less than 1000 gallons. A water tight containment shall be installed under all dispensers and at submersible pumps. A hydrostatic test must be performed on all containments. All steel piping for vents, risers, and fills in contact with the ground, backfill, or water shall be dielectrically wrapped or coated. A positive shut off valve shall be installed on pressurized product lines, at the submersibles, or installed at the tank for all suction piping systems. Vent piping is required to be tested from tank to grade level. All steel flex connectors in contact with ground, backfill or water shall have corrosion protection.
- **(6) SPECIAL CONTINGENCIES**: This permit replaces permit #00106-2013INS which was cancelled due to contractor missing final. There were no changed to original permit.

(7) PERSON, FIRM OR COMPANY PERFORMING WORK:

Neumayer Equipment Company, Inc. 5060 Arsenal Street Saint Louis, MO 63139 Contact Person: Rick McKay Phone: (314) 772-4501

Contractor Registration # IL-1502 Exp. 03/26/2014

Sincerely,

Daniel Starks

Daniel J. Starke

cc: Storage Tank Safety Specialist -Fire Department -Division File (Rev. - 9/10)