

## Office of the Illinois State Fire Marshal Division of Petroleum and Chemical Safety

1035 Stevenson Drive Springfield, IL 62703 2177851020

#### Amended

#### **FOR OFFICE USE ONLY**

Facility # 7046873 Permit # 01122-2019INS Request Rec'd 06/06/2019 Amended Date 06/12/2019 DS Approval Date 6/11/2019 DS Permit Expires 12/11/2019

## Permit for INSTALLATION of Underground Storage Tank(s) and Piping for Petroleum and Hazardous Substances.

Permission to install underground storage tank(s) or piping is hereby granted. Such installation must be in complete accordance with acceptable materials as specified in the Federal Register, Part II Environmental Protection Agency, 40 CFR Parts 280 and 281, and also with all sections of 41 Illinois Administrative Code, Parts 174, 175 and 176. The contractor the permit was issued to or an employee of that contractor (this does not include a subcontractor) shall submit a required job schedule for installation of underground storage tank(s) to the Office of the State Fire Marshal, Division of Petroleum and Chemical Safety. **THIS PERMIT IS VALID FOR SIX MONTHS FROM THE APPROVAL DATE.** 

(1) <u>OWNER OF TANKS</u> - Corporation, partnership, or other business

entity:

Meyer Oil Company 1505 W. Main Street Teutopolis, IL 62467

Contact: Michael Meyer (217) 703-1591

(2) FACILITY - name and address where tanks are located:

Mount Vernon Mach 1 1409 S. 42nd St. Mount Vernon, IL 62864

Contact: Alan Meyer (217) 703-1591

## (3) <u>INSTALLATION OF TANKS:</u>

- (a) Number and size of tanks being installed: (TK # 1, 5) 20,000, (TK # 2) 12,000, (TK # 3, 6) 8,000, (TK # 4) 10,000
- (b) Type of tank(s): (TK # 1, 2, 3, 4, 5) Tank Composite Double Wall Glasteel II, (TK # 6) Tank Fiberglass Double Wall Fluid Containment
- (c) Type of piping: (TK # 1, 2, 3) Piping Flexible Double Wall A.P.T. Poly Tech P200SC from tanks to dispensers as shown in site drawing, (TK # 1, 2, 3, 4, 5) Piping Other elbow fitting, (TK # 1, 2, 3, 4, 5) Piping Other Steel Riser, (TK # 1, 2, 3, 4, 5) Piping Other submersible pump, (TK # 1, 2, 3) Piping Chase Secondary Containment A.P.T. Poly Tech DCT-400, (TK # 1, 2, 3, 4, 5, 6) Piping Ball Valves, (TK # 1, 2, 3, 4, 5) Piping Shear Valves, (TK # 1, 2, 3, 4, 5) Piping Flex Connector Steel, (TK # 1, 2, 3, 4, 5) Piping Single Wall STP/Tanktop Sump Petroleum Containment Inc. 4500 Series, (TK # 4, 5) Piping Fiberglass Double Wall Ameron Dualoy 3000/LCX from tanks to dispensers as shown in site plan, (TK # 6) Piping Fiberglass Single Wall Piping Ameron Dualoy 3000L single wall vent piping fiberglass piping, (TK # 6) Piping Single Wall STP/Tanktop Sump Containment Solutions Fiberglass
- (d) Product to be stored in each tank: (TK # 1) Gasoline Regular, (TK # 2, 4, 5) Diesel Fuel, (TK # 3) Gasoline Premium, (TK # 6) Diesel Exhaust Fluid (Non-Regulated)
- (e) Type of leak detection being used:
  - Tank: (TK # 1, 2, 3, 4, 5, 6) Leak Detect Tank Automatic Tank Gauging Veeder Root TLS 450 Plus with CSLD, (TK # 1, 2, 3, 4, 5) Leak Detect Tank Interstitial Monitoring Veeder Root TLS 450 Plus
  - Piping: (TK # 1, 2, 3, 4, 5) Leak Detect Piping Electronic Pressurized Line Leak Detection Veeder Root TLS 450 Plus 8590 DPLLD, (TK # 1, 2, 3, 4) Leak Detect Piping Non-Discriminating Sump Sensor Interstitial Monitoring Veeder Root in all submersible and dispenser sumps. NOTE: Sensors must shut down the submersible pump supplying that line upon detection of a leak per 175.640 a) 1), (TK # 6) Leak Detect Piping Piping Sump Sensors Not Regulated Not Installed in submersible and dispenser sumps
- (f) Corrosion Protection being used:
  - Tank: (TK # 1, 2, 3, 4, 5) Corrosion Prot Tank Composite Non-Corrosive , (TK # 6) Corrosion Prot Tank Fiberglass Non-Corrosive
  - Piping: (TK # 1, 2, 3) Corrosion Prot Piping Flexible Non-Corrosive , (TK # 4, 5, 6) Corrosion Prot Piping Fiberglass Non-Corrosive
- (g) Spill containment devices, piping and dispenser containment devices: (TK # 1, 2, 3, 4, 5) Spill Contain Device Single Wall Spill Bucket OPW 1-2100 PEVR, (TK # 6) Spill Contain Device Field Constructed

- (h) Overfill prevention devices: (TK # 1, 2, 3, 4, 5) Overfill Prev Device Overfill Drop Tube Valve OPW 71SO-400CTB, (TK # 6) Overfill Prev Device Overfill Alarm Veeder Root TLS 450plus
- (4) The owner must notify this Office when completion of tank installation has occurred, on the Notification for Underground Storage Tank Form and the licensed contractor must submit the required job schedule for installation to the OSFM prior to the work being performed. Both forms can be obtained at www.sfm.illinois.govor by calling (217)785-1020.
- (5) GENERAL REQUIREMENTS: There shall be a minimum of two manufactured slotted or perforated observation wells of at lease 4 inches in diameter, installed in each new tank field of tanks larger than 1000 gallons and one well for tanks less than 1000 gallons. A water tight containment shall be installed under all dispensers and at submersible pumps. A hydrostatic test must be performed on all containments. All steel piping for vents, risers, and fills in contact with the ground, backfill, or water shall be dielectrically wrapped or coated. A positive shut off valve shall be installed on pressurized product lines, at the submersibles, or installed at the tank for all suction piping systems. Vent piping is required to be tested from tank to grade level. All steel flex connectors in contact with ground, backfill or water shall have corrosion protection.

# (6) <u>SPECIAL CONTINGENCIES</u>:

Error made on what was submitted.

Truck diesel piping is 3" LCX FRP piping

### (6) PERSON, FIRM OR COMPANY PERFORMING WORK:

UPC Enterprises, LC d/b/a United Petroleum Service 4444 Union Blvd. St. Louis, MO 63115

Contact Person: Harvey Stokes Phone: (314) 241-3767

Contractor Registration # IL002402 Exp. 2/10/2020

Sincerely,

Daniel Starks

Daniel J. Starke

cc: Storage Tank Safety Specialist Division File