


Probe Description & Product Application
Stainless Steel Mag Plus In-Tank Probe for Monitoring Alternative Fluids with No Water Detection in both USTs and ASTs
Specific Products Monitored / Product Compatibility
Part # & Description
Approved Products
Monitoring Functionality Options
Leak Detection / BIR - Accuchart Probes

1. 846397-4XX Stainless Steel (SS) In-Tank Probe with High Grade Polymer (HGP) Canister with No Water Detection & 0.1 GPH Testing Capability, UL
2. 846397-5XX SS In-Tank Probe with HGP Canister with No Water Detection & 0.2GPH Testing Capability, UL
3. 846391-4XX SS In-Tank Probe with Aluminum (AL) Canister with No Water Detection & 0.1 GPH Testing Capability, UL
4. 846391-5XX SS In-Tank Probe with AL Canister with No Water Detection & 0.2 GPH Testing Capability, UL

Alcohol (<=100% Alcohol)*

A. 0.1 GPH static in-tank testing for USTs only

Fuel Oil #6

B. 0.2GPH static in-tank testing for USTs only

Propylene Glycol

Methyl Alcohol*

C. 0.2 GPH Continuous Statistical Leak Detection (CSLD) for USTs only

Methanol (<=100% Alcohol)*

D. No Leak Detection / Inventory Only for USTs & ASTs

ETBE (<=100% Ether)

E. BIR - Accuchart for USTs only

Ethanol (<=100% Alcohol) includes E85*

* Limited to E85 for ATEX probes

MTBE (<=100% Ether)

Used Oil

Ethylene Glycol

Windshield Washer Fluid

DEF (AdBlue)

No Leak Detection/Inventory Only Probes

1. 846397-6XX SS with HGP Canister with No Water Detection & No Leak Detection/ Inventory Only, UL
2. 846391-6XX SS with AL Canister with No Water Detection & No Leak Detection/ Inventory Only, UL

Console Compatibility
Maximum Probes / Console
Probe Interface Modules
Module Part #
Module Description
of Modules per Console
of Probe Inputs per Module
Availability

TLS-450PLUS (8600 Series) with TLS-XB installed (3 max per system)

64 (32 with BIR)

332812-001

Universal Sensor Module (USM) Interface for Probes, Sensors, and DPLLD

Up to 4

16

Sold Separately (either Factory Installed or as a Spare Module)

TLS4i (8601 Series)

4

TLS4c (8601 Series)

2

No module required, probe input capability factory installed

TLS-350/R/PLUS

16

329356-002

4-Input Probe Interface Module

4

4

Sold Separately (either Factory Installed or as a Spare Module)

TLS-300i

4

TLS-300C

2

No module required, probe input capability factory installed