

Probe Description & Product Application	Stainless Steel Mag Plus In-Tank Probe for Monitoring Alternative Fluids with No Water Detection in both USTs and ASTs						
Specific Products Monitored / Product Compatibility	Part # & Description		Approved Products		Monitoring Functionality Options		
	Leak Detection / BIR - Accuchart Probes 1. 846397-4XX Stainless Steel (SS) In-Tank Probe with High Grade Polymer (HGP) Canister with No Water Detection & 0.1 GPH Testing Capability, UL 2. 846397-5XX SS In-Tank Probe with HGP Canister with No Water Detection & 0.2GPH Testing Capability, UL 3. 846391-4XX SS In-Tank Probe with Aluminum (AL) Canister with No Water Detection & 0.1 GPH Testing Capability, UL 4. 846391-5XX SS In-Tank Probe with AL Canister with No Water Detection & 0.2 GPH Testing Capability, UL No Leak Detection/Inventory Only Probes 1. 846397-6XX SS with HGP Canister with No Water Detection & No Leak Detection/ Inventory Only, UL 2. 846391-6XX SS with AL Canister with No Water Detection & No Leak Detection/ Inventory Only, UL		Alcohol (<=100% Alcohol)*		A. 0.1 GPH static in-tank testing for USTs only		
			Fuel Oil #6		B. 0.2GPH static in-tank testing for USTs only		
			Propylene Glycol		C. 0.2 GPH Continuous Statistical Leak Detection (CSLD) for USTs only		
			Methyl Alcohol*				
			Methanol (<=100% Alcohol)*		D. No Leak Detection / Inventory Only for USTs & ASTs		
			ETBE (<=100% Ether)		E. BIR – Accuchart for USTs only		
			Ethanol (<=100% Alcohol) includes E85*		* Limited to E85 for ATEX probes		
			MTBE (<=100% Ether)				
			Used Oil				
			Ethylene Glycol				
			Windshield Washer Fluid				
			DEF (AdBlue)				
Console Compatibility	Maximum Probes / Console	Probe Interface Modules					
		Module Part #	Module Description	# of Modules per Console	# of Probe Inputs per Module	Availability	
	TLS-450PLUS (8600 Series) with TLS-XB installed (3 max per system)	64 (32 with BIR)	332812-001	Universal Sensor Module (USM) Interface for Probes, Sensors, and DPLLD	Up to 4	16	Sold Separately (either Factory Installed or as a Spare Module)
	TLS4i (8601 Series)	4	No module required, probe input capability factory installed				
	TLS4c (8601 Series)	2					
TLS-350/R/PLUS	16	329356-002	4-Input Probe Interface Module	4	4	Sold Separately (either Factory Installed or as a Spare Module)	
TLS-300i	4	No module required, probe input capability factory installed					
TLS-300C	2						