Internal Dimension as Standard 633T Adaptors -- To minimize pressure drop and maximize flow rates for quick product delivery. 61SALP-MA - EVR Approved for use with E85 61SALP Adaptor: bronze Base: bronze Retaining ring: conductive nylon Set screws

OPW 21Ge™ Series Ethanol Nozzles (/products/temporary-/opw-21ge-series-ethanol-nozzles)

/products/temporary-/opw-21ge-series-ethanol-nozzles

3/4" F (NPT) 19 F x 19 F 0.6 0.27 Valve for up to E85 / 300 lb. □65V Series 3/4

10 Plus Series Emergency Shut-Off Valves (/products/us/retail-fueling-products/below-ground-products/underground-storage-tank-equipment/emergency-shear-valves/10-plus-series-emergency-shut-off-valves)

/products/us/retail-fueling-products/below-ground-products/underground-storage-tank-equipment/emergency-shear-valves/10-plus-series-emergency-shut-off-valves

Double Pressure Combination E85 10P-0152E85 1-1/2" 4 6.8 3.10 NPT Double

1 2 3 4 5
(http://[redacted]/search-resultsresultsresultsresults-retailRetail/[redacted]/57
Index[redacted]=0)

Copyright ©2009-2018
OPW, A Dover Company (http://www.dovercorporation.com)

The following U.S. patents have expired:
4,199,012; 4,351,375; 4,429,725; 4,505,308; 4,453,578; 4,497,350; 4,557,302; 4,649,969; 4,682,714; 4,825,914; 4,971,121; 5,007,468; 5,135,029.
OPW claims no rights in any patent beyond its expiration.