

SPECIFICATIONS CONTINUED

Approvals/Certifications

- ULC Listed (grade level CI-GKT versions only).
- CARB approved (grade level only).
- Exceeds H20 and HS20 load standards (maximum axle load requiring support for the 32,000 or 16,000 pounds for each set of dual tire wheels).

ORDERING INFORMATION

Ordering Guide

Complete spill container part numbers have a specific order and are created using the following guidelines:

705 XXXY A B C

XXX = Containment Options

- 545 = Grade level single wall
- 555 = Grade level double wall
- 556 = Below grade double wall

Y = Interstitial Monitoring Options

- 0 = No sensor
- 1 = Visual monitor (float gauge)
- 2 = Electronic sensor monitor

A = Base Thread Options

- 0 = NPSM
- 1 = NPT
- 2 = BSPT

B = Drain Options

- 1 = With drain
- 2 = Without drain

C = Lid/Cover

- BLK = Black fiberglass 18" manway cover (below grade only)
- CI-GKT = Black epoxy-coated cast iron gasketed lid (grade level only)
- CI-GRN = Green epoxy-coated cast iron gasketed lid (grade level only)
- CI-ORG = Orange epoxy-coated cast iron gasketed lid (grade level only)
- CI-RED = Red epoxy-coated cast iron gasketed lid (grade level only)
- CI-WHT = White epoxy-coated cast iron gasketed lid (grade level only)
- CI-YEL = Yellow epoxy-coated cast iron gasketed lid (grade level only)

Example: **705555111CI-GKT** = Defender Series® grade level double wall spill container with visual monitor, with NPT base thread, with drain and with black cast iron gasketed lid.

Example: **705556211BLK** = Defender Series® below grade double wall spill container with electronic sensor monitor, with NPT base thread, with drain and with black fiberglass manway cover (manway included).

Defender Series® Spill Containers Common Configurations

| Model | Description |
|-----------------|---|
| 705545001CI-GKT | Defender Series® grade level, single wall, NPSM thread, with drain, with black epoxy-coated cast iron gasketed lid |
| 705545002CI-GKT | Defender Series® grade level, single wall, NPSM thread, without drain, with black epoxy-coated cast iron gasketed lid |
| 705545011CI-GKT | Defender Series® grade level, single wall, NPT thread, with drain, with black epoxy-coated cast iron gasketed lid |
| 705545012CI-GKT | Defender Series® grade level, single wall, NPT thread, without drain, with black epoxy-coated cast iron gasketed lid |
| 705545021CI-GKT | Defender Series® grade level, single wall, BSPT thread, with drain, with black epoxy-coated cast iron gasketed lid |
| 705545022CI-GKT | Defender Series® grade level, single wall, BSPT thread, without drain, with black epoxy-coated cast iron gasketed lid |
| 705555101CI-GKT | Defender Series® grade level, double wall, NPSM thread, with drain, with visual monitor, with black epoxy-coated cast iron gasketed lid |
| 705555102CI-GKT | Defender Series® grade level, double wall, NPSM thread, without drain, with visual monitor, with black epoxy-coated cast iron gasketed lid |
| 705555111CI-GKT | Defender Series® grade level, double wall, NPT thread, with drain, with visual monitor, with black epoxy-coated cast iron gasketed lid |
| 705555112CI-GKT | Defender Series® grade level, double wall, NPT thread, without drain, with visual monitor, with black epoxy-coated cast iron gasketed lid |
| 705555211CI-GKT | Defender Series® grade level, double wall, NPT thread, with drain, with electronic sensor monitor, with black epoxy-coated cast iron gasketed lid |
| 705555212CI-GKT | Defender Series® grade level, NPT thread, without drain, with electronic sensor monitor, with black epoxy-coated cast iron gasketed lid |
| 705556111BLK | Defender Series® below grade, double wall, NPT thread, with drain, with visual monitor, with black fiberglass manway cover (18" manway included) |
| 705556112BLK | Defender Series® below grade, double wall, NPT thread, no drain, with visual monitor, with black fiberglass manway cover (18" manway included) |
| 705556211BLK | Defender Series® below grade, double wall, NPT thread, with drain, with electronic sensor monitor, with black fiberglass manway cover (18" manway included) |
| 705556212BLK | Defender Series® below grade, double wall, NPT thread, no drain, with electronic sensor monitor, with black fiberglass manway cover (18" manway included) |
| 705559901* | Defender Series® grade level cutaway display, double wall, with drain, with visual monitor |

*For display and demonstration purposes only. Six to eight week lead time.

Defender Series® Spill Container Installation Tools

| Model | Description |
|--------|---|
| T-7001 | T-handle wrench |
| T-7106 | Double-ended installation tool |
| T-7107 | Double wall vacuum test kit (for double wall models only) |