

CERTIFICATE OF COMPLIANCE

Certificate Number 20190425-MH1821
Report Reference MH1821-20121003
Issue Date 2019-APRIL-25

Issued to: WAYNE FUELING SYSTEMS LLC
3814 JARRETT WAY
AUSTIN TX 78728

**This certificate confirms that
representative samples of**

FLAMMABLE LIQUID DISPENSING DEVICES, POWER
OPERATED

See Addendum Page for Models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:
Additional Information:

See Addendum Page for Standards

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20190425-MH1821
Report Reference MH1821-20121003
Issue Date 2019-APRIL-25

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models:

Power-operated flammable liquid dispensing devices, Helix Series,

Remote Control Models H or S, followed by N, W or L followed by LM, LU or I followed by 1, 2, 3 or 4, followed by 1, 2, 3, 4 or 5, followed by 1, 2, 3 or 4, followed by 1 or 2, followed by M, P and/or R, V, may be followed by XL3.

Remote Control Models H, followed by N or W, followed by LM or LU, followed by 3 or 4, followed by 5, followed by 3 or 4, followed by 3, followed by E, followed by M, P, and/or R. Suitable for use with E85, may be followed by XL3.

Remote Control Models H or S, followed by N, W, or W, followed by LM, LU, or I, followed by 1, 2, 3, or 4, followed by 1, 2, 3, 4, or 5, followed by 1, 2, 3, or 4, followed by 1 or 2, followed by K, followed by M, P, and/or R, may be followed by XL3. Suitable for use with E25 and B20.

Self-Contained (Suction) Models H or S, followed by N, W or L followed by LM, LU or I followed by 1, 2, 3 or 4, followed by 1, 2, 3, 4 or 5, followed by 1, 2, 3 or 4, followed by 1 or 2, followed by S with or without M and/or P, may be followed by XL3.

Standards for Safety:

UL 87, Power-Operated Dispensing Devices For Petroleum Products;
UL 1238, Control Equipment for Use With Flammable Liquid Dispensing Devices;
UL 121201, Nonincendive Electrical Equipment for use in Class I and II, Division 2 And Class III, Divisions 1 and 2 Hazardous (Classified) Locations;
UL 87A, Power-Operated Dispensing Devices for Gasoline and Gasoline/Ethanol Blends with Nominal Ethanol Concentrations up to 85 Percent (E0 - E85);
UL 87B, Power-Operated Dispensing Devices for Diesel Fuel, Biodiesel Fuel, Diesel/Biodiesel Blends with Nominal Biodiesel Concentrations Up to 20 Percent (B20), Kerosene, and Fuel Oil



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

