

Home → Products → Pipe Thread Sealants → Gasola® E-Seal Thread Sealant



Gasola® E-Seal Thread Sealant



Non-hardening, non-toxic, opaque, dark green paste designed specifically for ethanol blended gasoline including E10 and E85 (for 100% ethanol or 100% methanol applications - use Gasola 100).

Provides a positive seal on pipe threads, joints, fittings, hoses, nozzles, pump assemblies, oil burners, hydraulics, bolts, compressors, engines, motors, fuel lines and couplings.

For use on brass, copper, stainless steel, aluminum, black pipe, tin and galvanized pipe.

Excellent resistance to gasoline, ethanol blended gasoline such as E10 and E85, petroleum solvents, kerosene diesel oil, BioDiesel propane, jet fuels, butane, LPG, cutting oils, ammonia, aliphatic solvents, acids, steam and potable water.

NOT for use on oxygen.

Temperature Range: -100°F to 600°F (-74°C to 318°C).

Pressure Range: Up to 10,000 psi when sealing liquids and up to 3,000 psi with gases.

One year shelf life.

Distributors

Translated Information for Download



Related < >



Fast Anaer Seal



Gasol Thread PTFE



Gasol Thread

Additional Info

Data Sheets

FPC Stock Code	Container Size	Units per Case
GE04	1/4 pt. Brush	24
GE08	1/2 pt. Brush	24
GE16	1 pt. Brush	12