


Probe Description & Product Application	<p style="text-align: center;">Stainless Steel Mag Plus In-Tank Probe for Monitoring Alternative Fluids with No Water Detection in both USTs and ASTs</p>					
Specific Products Monitored / Product Compatibility	Part # & Description	Approved Products	Monitoring Functionality Options			
	<p>Leak Detection / BIR - Accuchart Probes</p> <ol style="list-style-type: none"> 846397-4XX Stainless Steel (SS) In-Tank Probe with High Grade Polymer (HGP) Canister with No Water Detection & 0.1 GPH Testing Capability, UL 846397-5XX SS In-Tank Probe with HGP Canister with No Water Detection & 0.2GPH Testing Capability, UL 846391-4XX SS In-Tank Probe with Aluminum (AL) Canister with No Water Detection & 0.1 GPH Testing Capability, UL 846391-5XX SS In-Tank Probe with AL Canister with No Water Detection & 0.2 GPH Testing Capability, UL <p>No Leak Detection/Inventory Only Probes</p> <ol style="list-style-type: none"> 846397-6XX SS with HGP Canister with No Water Detection & No Leak Detection/ Inventory Only, UL 846391-6XX SS with AL Canister with No Water Detection & No Leak Detection/ Inventory Only, UL 	Alcohol (<=100% Alcohol)*	A. 0.1 GPH static in-tank testing for USTs only			
		Fuel Oil #6	B. 0.2GPH static in-tank testing for USTs only			
		Propylene Glycol	C. 0.2 GPH Continuous Statistical Leak Detection (CSLD) for USTs only			
		Methyl Alcohol*				
		Methanol (<=100% Alcohol)*	D. No Leak Detection / Inventory Only for USTs & ASTs			
		ETBE (<=100% Ether)	E. BIR – Accuchart for USTs only			
		Ethanol (<=100% Alcohol) includes E85*	* Limited to E85 for ATEX probes			
		MTBE (<=100% Ether)				
		Used Oil				
		Ethylene Glycol				
		Windshield Washer Fluid				
DEF (AdBlue)						
Console Compatibility	Maximum Probes / Console	Probe Interface Modules				
		Module Part #	Module Description	# of Modules per Console	# of Probe Inputs per Module	Availability
TLS-450PLUS (8600 Series) with TLS-XB installed (3 max per system)	64 (32 with BIR)	332812-001	Universal Sensor Module (USM) Interface for Probes, Sensors, and DPLLD	Up to 4	16	Sold Separately (either Factory Installed or as a Spare Module)
TLS4i (8601 Series)	4	No module required, probe input capability factory installed				
TLS4c (8601 Series)	2					
TLS-350/R/PLUS	16	329356-002	4-Input Probe Interface Module	4	4	Sold Separately (either Factory Installed or as a Spare Module)
TLS-300i	4	No module required, probe input capability factory installed				
TLS-300C	2					