



XP FLEXIBLE PIPEWORK

APT™ XP pipework provides a highly flexible pipework solution that makes installation simple and easy in any weather condition or site configuration. XP pipework can be used in both pressure and suction applications, and is ideal for underground service station fuel delivery systems. The XP pipework system features controlled flexibility, even in low temperatures, permitting fast, easy installation.

Reel Size	Inches*	cm*
Master	91 x 33 x 74	231.1 x 83.8 x 187.9
Super Master (S. Mast.)	91 x 52 x 74	231.1 x 132.1 x 187.9

*Reel dia. x width x hub dia.

HIGHLIGHTS

- Available in 1", 1½", 1¾" and 2" diameters in a variety of coil lengths.
- The D-Series piping is a single wall, direct bury piping.
- The SC-Series piping provides additional environmental security as a secondary contained direct bury pipe.
- XP pipe features a 3 ft. bend radius for all pipe diameters making it one of the most flexible, yet durable fuel pipes available.
- No possibility of piping layer delamination due to the layered piping construction of high-grade material.
- With long coils (1000+ ft.) and simple fittings, XP pipework can be installed quickly without specialized tools in any weather.

SPECIFICATIONS

- Primary layer construction of Nylon 12 - the fuel line material contains no polyethylene.
- Do not store piping in direct sunlight.

Approvals/Certifications

- UL971 listed.
- Biofuel compatible (E85 and Biodiesel).

ORDERING INFORMATION

Model	Description	Ft.	Reel	Weight	
				Lbs.	
XP-100-SC	1" secondary contained	250	Master	301	
		500	Master	408	
		2500	S. Master	1299	
XP-100-D	1" single wall	250	Master	258	
		500	Master	320	
		100	Master	250	
XP-150-SC	1½" secondary contained	250	Master	333	
		500	Master	470	
		1,000	S. Master	789	
		1,500	S. Master	1061	
		100	Master	225	
XP-150-D	1½" single wall	250	Master	270	
		500	Master	570	
		1,000	S. Master	536	
XP-175-SC	1¾" secondary contained	1,500	S. Master	686	
		100	Master	300	
		250	Master	405	
		500	Master	580	
		1,000	S. Master	1076	
XP-200-SC	2" secondary contained	250	Master	552	
		500	S. Master	914	
XP-200-D	2" single wall	250	Master	427	
		500	S. Master	664	