


<b>Probe Description &amp; Product Application</b>	Mag Plus In-Tank Probe for Monitoring Light & Heavy Oil Products with & without Water Detection in both USTs and ASTs									
<b>Specific Products Monitored / Product Compatibility</b>	<b>Part # &amp; Description</b>	<b>Approved Products (Use with Light Oil Float Kit)</b>	<b>Monitoring Functionality Options</b>							
	<u>No Leak Detection/Inventory Only Probes with Water Detection</u> 1. 0846397-3xx Stainless Steel (SS) In-Tank Probe with High Grade Polymer (HGP) Canister with Water Detection & No Leak Detection/Inventory Only, UL	Bio Diesel (High Density – Specific Gravity > 0.865) * Fuel Oil #4 Motor Oil ** Gear Oil, 90W	No Leak Detection / Inventory Only							
	<u>No Leak Detection/Inventory Only Probes with No Water Detection</u> 1. 0846397-6xx SS In-Tank Probe with HGP Canister with No Water Detection & No Leak Detection/Inventory Only, UL	Toluene Transmission Fluid								
	<b>Probe Interface Modules</b>									
	<b>Console Compatibility</b>	<b>Maximum Probes / Console</b>					<b>Module Part #</b>	<b>Module Description</b>	<b># of Modules per Console</b>	<b># of Probe Inputs per Module</b>
TLS-450PLUS (8600 Series) with TLS-XB installed (3 max per system)	64	0332812-001					Universal Sensor Module (USM) Interface for Probes, Sensors, and DPLLD	Up to 4	16	Sold Separately (either Factory Installed or as a Spare Module)
TLS4 (8601 Series)	12	No module required, probe input capability factory installed								
TLS4B (8601 Series)	6									
TLS-350/R/PLUS	16	0329356-002	4-Input Probe Interface Module	4	4	Sold Separately (either Factory Installed or as a Spare Module)				
TLS-300i	4	No module required, probe input capability factory installed								
TLS-300C	2									
<b>Float Installation Kits</b>	<b>Part # &amp; Description</b>	<b>Float Size</b>	<b>Cable Lengths</b>		<b>Min/Max Probe Length</b>					
	0846400-0x4 Mag Plus Alternative Fluids Float Kit – No Water Float	4" (10.16cm)	5' (1.5m), 10' (3.05m)		48" (1.2m) - 144" (3.66m)					
	0846400-1x4 Mag Plus Alternative Fluids Float Kit – No Water Float	2" (5.08cm)								
	0846400-002 Light Oil	4" (10.16cm)								
	0846400-102 Light Oil	2" (5.08cm)								
	0846400-007 Heavy Oil	4" (10.16cm)								
	0846400-107 Heavy Oil	2" (5.08cm)								

\* Tank testing approved for: B6-B20 meeting ASTM D7467 and B100 meeting ASTM D6751

\*\* Compatible with tank testing