

Steelflex Ultra Hardwall

Gasoline Hose



Steelflex Ultra Hardwall
Gasoline Hose



APPLICATION:

A heavy Duty non-collapsible hardwall hose for dispensing gasoline, this construction has minimal cubical expansion Handles 50% aromatic hydrocarbons and unleaded gasoline.

TUBE:

Gasoline-resistant Nitrile.

REINFORCEMENT:

High-tensile Wire Braid.

COVER:

Black abrasion, oil and weather-resistant blend of Nitrile/PVC.

COUPLINGS:

Coupled to specifications with IRPCO curb pump hose couplings.

ALSO AVAILABLE IN:

* 5/8" red, green or yellow - 3/4" red, blue, green or yellow.

* 25% upcharge for colored hose

ID In.	OD In.	BRAID	W.P. PSI	WEIGHT Lb./Ft.
5/8"	1"	1Wire	50	.38
3/4"	1.13"	1Wire	50	.43
1"	1.36"	1Wire	50	.58



www.Irpco.net

THE NAME YOU TRUST FOR
SERVICE AND QUALITY SINCE 1973.

Flexsteel® Futura™

Ethan-ALL™ Gasoline Hose



APPLICATION:

Flexsteel® Futura™ Ethan-ALL™ dispensing hose assembly is for use in ethanol dispensing applications up to E85. This new assembly provides the quality Futurin™ cover with its superior ozone resistance along with a new premium layline. The tube construction meets the E25/E85 compatibility test requirements of UL87A.

TUBE:

Nitrile synthetic rubber.

REINFORCEMENT:

Wire braid.

COVER:

Futurin™ synthetic rubber with yellow stripe.

TEMPERATURE:

-40°F to 140°F

BRANDING:

Example:
3/4" cRUUS Continental® Flexsteel® Futura™ Ethan-ALL™ E85 559N Made in USA

ID In.	OD In.	W.P. PSI	WEIGHT Lb./Ft.
3/4"	1.13"	50	0.46