


Probe Description & Product Application	Stainless Steel Mag Plus In-Tank Probe for Monitoring Alternative Fluids with No Water Detection in both USTs and ASTs	
--	---	---

	Part # & Description	Approved Products	Monitoring Functionality Options
Specific Products Monitored / Product Compatibility →	Leak Detection / BIR – Accuchart Probes 1. 0846397-4xx Stainless Steel (SS) In-Tank Probe with High Grade Polymer (HGP) Canister with No Water Detection & 0.1 GPH Testing Capability, UL 2. 0846397-5xx SS In-Tank Probe with HGP Canister with No Water Detection & 0.2GPH Testing Capability, UL No Leak Detection/Inventory Only Probes 1. 0846397-6xx SS with HGP Canister with No Water Detection & No Leak Detection/ Inventory Only, UL →	Alcohol (<=100% Alcohol) *	A. 0.1 GPH static in-tank testing for USTs only
		Fuel Oil #6 **	B. 0.2GPH static in-tank testing for USTs only
		Propylene Glycol **	C. 0.2 GPH Continuous Statistical Leak Detection (CSLD) for USTs only
		Methyl Alcohol *	
		Methanol (<=100% Alcohol) *	D. No Leak Detection / Inventory Only for USTs & ASTs
		ETBE (<=100% Ether)	E. BIR – Accuchart for USTs only
		Ethanol (<=100% Alcohol) includes E85 *	
		MTBE (<=100% Ether)	
		Used Oil	
		Ethylene Glycol **	
		Windshield Washer Fluid **	
		DEF (AdBlue) **	
* Limited to 85% for ATEX probes ** These products are not approved for leak detection			

Console Compatibility	Maximum Probes / Console	Probe Interface Modules				
		Module Part #	Module Description	# of Modules per Console	# of Probe Inputs per Module	Availability
TLS-450PLUS (8600 Series) with TLS-XB installed (3 max per system)	64 (32 with BIR)	0332812-001	Universal Sensor Module (USM) Interface for Probes, Sensors, and DPLLD	Up to 4	16	Sold Separately (either Factory Installed or as a Spare Module)
TLS4 (8601 Series)	12	No module required, probe input capability factory installed				
TLS4B (8601 Series)	6					
TLS-350/R/PLUS	16	0329356-002	4-Input Probe Interface Module	4	4	Sold Separately (either Factory Installed or as a Spare Module)
TLS-300i	4	No module required, probe input capability factory installed				
TLS-300C	2					