

£85
STP A6 R 75

Ordering Information continued

Standard 2 Hp Fixed Speed Submersible Turbine Pumps

Model	Description	Model Length Range Number	Model Length Range*
STPM200-VL1	2 Hp fixed speed with MagShell™	VL1	63"-91"
STPM200-VL2	2 Hp fixed speed with MagShell™	VL2	94"-154"
STPM200-VL3	2 Hp fixed speed with MagShell™	VL3	126"-217"
STPHM200-VL1	2 Hp high pressure fixed speed with MagShell™	VL1	63"-92"
STPHM200-VL2	2 Hp high pressure fixed speed with MagShell™	VL2	94"-155"
STPHM200-VL3	2 Hp high pressure fixed speed with MagShell™	VL3	126"-218"

Alcohol-Gas (AG) 2 Hp Fixed Speed Submersible Turbine Pumps

Model	Description	Model Length Range Number	Model Length Range*
STPAGM200-VL1	2 Hp AG fixed speed with MagShell™	VL1	63"-91"
STPAGM200-VL2	2 Hp AG fixed speed with MagShell™	VL2	94"-154"
STPAGM200-VL3	2 Hp AG fixed speed with MagShell™	VL3	126"-217"
STPAGHM200-VL1	2 Hp AG high pressure fixed speed with MagShell™	VL1	63"-92"
STPAGHM200-VL2	2 Hp AG high pressure fixed speed with MagShell™	VL2	94"-155"
STPAGHM200-VL3	2 Hp AG high pressure fixed speed with MagShell™	VL3	126"-218"

Notes:

1. Remove "M" from model number for non-MagShell™ pump motor assembly.
2. STP models are compatible with fuel mixtures containing up to 10% ethanol with gasoline, diesel fuels, and 20% MTBE, 20% ETBE or 17% TAME with gasoline. STPAG models are compatible with fuel mixtures containing diesel fuel with up to 20% biodiesel, 100% biodiesel, up to 85% ethanol with gasoline, and 20% MTBE, 20% ETBE or 17% TAME with gasoline.
3. All models are supplied with a standard check valve unless factory option "R" or "W" is specified.
4. All above models require single-phase, 208-230 VAC, 60 Hz incoming power.
5. 4" riser pipe, if supplied locally, must be 4½" OD by 3/16" WT tubing.
6. For riser pipe lengths 31" to 69", additional charges apply.

*Model length (A) defined as the dimension from turbine manifold bottom to pump motor inlet.

Factory Installed Options

Specified in model number at time of STP order.

Model	Description
F	Floating suction adapter, 1½" NPT female, must be factory installed
K	IFS (intake filter screen) factory assembled to pump motor assembly
R	Model R check valve, factory installed, for Veeder-Root™ PLLD Line Leak
W	Model W check valve, factory installed, for Red Jacket PPM4000 Line Leak