

Magnetostrictive Probes for Alternative Fluids

Certified performance for inventory control and in-tank leak detection in fuel blends up to **100% alcohol**

Veeder-Root offers two types of Magnetostrictive Probes for Alternative Fluids to provide highly accurate, trouble-free in-tank leak detection and inventory control in fluids of up to 100% alcohol. The Magnetostrictive Probe for Alternative Fluids with water detection is ideal for fuel blends with less than 20% alcohol. The Magnetostrictive Probe for Alternative Fluids without water detection has been developed for fluids up to 100% alcohol.

Series 8463 0.1 GPH Mag Probe for Alternative Fluids

The 0.1 GPH Mag Probe for Alternative Fluids has been third-party tested and certified to perform far better than the U.S. E.P.A. standards for both 0.1 GPH volumetric tank tightness testing and 0.2 GPH automatic tank gauging. (See the summary of leak test performance on back or call us for a copy of the complete test results.)

0.1 GPH Mag Probe and CSLD — Leak detection without shutting down your tanks!

CSLD, Continuous Statistical Leak Detection, is an advanced tank testing technology that makes full use of the TLS-300 and TLS-350(R)'s in-tank monitoring capabilities. CSLD eliminates the need for tank shutdown to perform a leak test — no lost business, no lost operating time!

The TLS-300 and TLS-350(R) equipped with CSLD use the 0.1 GPH Mag Probe to continuously monitor fuel height and temperature information to detect idle times in the tank. During each idle time, data collected forms a highly accurate leak detection database. Sophisticated statistical analysis techniques in CSLD constantly evaluate the database to discard invalid data and perform leak tests based on only high-quality information in the current database. In fact, a new leak test is performed every time new data from an idle period is added.

Series 8463 0.2 GPH Mag Probe for Alternative Fluids

The 0.2 GPH Mag Probe for Alternative Fluids provides the same reliable inventory control features and fluid compatibility as the 0.1 GPH Mag Probe for Alternative Fluids, but offers 0.2 GPH leak detection at a lower cost.

The 0.2 GPH Mag Probe for Alternative Fluids has also been third-party tested and certified to exceed U.S. E.P.A. standards for 0.2 GPH automatic tank gauging. (See the summary of leak test performance on back or call us for a copy of the complete test results.)

Approved for Aboveground Tank Applications

Veeder-Root Magnetostrictive Probes are approved for use in aboveground storage tanks to monitor fuel inventory. An AST installation Kit (Form Number 312020-984) is required for these applications and is available from Veeder-Root, Customer Service 800-873-3313 or your authorized Veeder-Root distributor.

Magnetostrictive Probes for Alternative Fluids are available in 0.1 GPH and 0.2 GPH Versions

Features & Benefits

- Non-corrosive, stainless steel tubing for long-life monitoring in fuels up to **100% alcohol**
- Highly accurate Magnetostrictive measurement technology
- Fast accurate leak tests
- 0.1 GPH Mag Probe for Alternative Fluids is third-party certified to exceed U.S. E.P.A. performance standards for 0.1 GPH Volumetric Tank Tightness Testing
- 0.1 GPH Mag Probe for Alternative Fluids is compatible with TLS-300 and TLS-350R with CSLD for continuous statistical leak detection
- 0.2 GPH Mag Probe for Alternative Fluids is third-party certified to exceed U.S. E.P.A. performance standards for 0.2 GPH Automatic Tank Gauging
- 2", 3" and 4" Float Kits available

Probe Models

Tank I.D.	Mag Plus Probes for Alternative Fluids with Water Detection Part No*			Mag Plus Probes for Alternative Fluids without Water Detection Part No*		
	0.1 GPH Leak Detection	0.2 GPH Leak Detection	Inventory Only	0.1 GPH Leak Detection	0.2 GPH Leak Detection	Inventory Only
4'	846391-101	846391-201	846391-301	846391-401	846391-501	846391-601
5'	846391-102	846391-202	846391-302	846391-402	846391-502	846391-602
5'4"	846391-103	846391-203	846391-303	846391-403	846391-503	846391-603
6'	846391-104	846391-204	846391-304	846391-404	846391-504	846391-604
7'	846391-105	846391-205	846391-305	846391-405	846391-505	846391-605
7'6"	846391-106	846391-206	846391-306	846391-406	846391-506	846391-606
8'	846391-107	846391-207	846391-307	846391-407	846391-507	846391-607
9'	846391-108	846391-208	846391-308	846391-408	846391-508	846391-608
9'6"	846391-117	846391-217	846391-317	846391-417	846391-517	846391-617
10'	846391-109	846391-209	846391-309	846391-409	846391-509	846391-609
10'6"	846391-110	846391-210	846391-310	846391-410	846391-510	846391-610
11'	846391-111	846391-211	846391-311	846391-411	846391-511	846391-611
12'	846391-112	846391-212	846391-312	846391-412	846391-512	846391-612
2.0M	846391-113	846391-213	846391-313	846391-413	846391-513	846391-613
2.5M	846391-114	846391-214	846391-314	846391-414	846391-514	846391-614
2.67M	846391-116	846391-216	846391-316	846391-416	846391-516	846391-616
3.0M	846391-115	846391-215	846391-315	846391-415	846391-515	846391-615
Custom Length	846391-199	846391-299	846391-399	846391-499	846391-599	846391-699

*Float kits must be ordered separately from probes, water floats not recommended for fuel blends with >20% alcohol

Floats Match Table

Product	Probe	Functions	Float Kit
Gasoline (<=20% Alcohol)	Mag Plus Probe for Alternative Fluids with Water Detection P/N 846391-1xx or -2xx	Inventory: Yes Leak Detection: Yes Water detection: Yes	Gasoline Float Kit P/N 846400-xy0* (*see note for definition of xy below)
	Inventory Only Mag Plus Probe for Alternative Fluids with Water Detection P/N 846391-3xx	Inventory: Yes Leak Detection: No Water detection: Yes	
Alcohol / Ethanol (<=100% Alcohol, including E85) Methanol (<=100% Alcohol) ETBE (<=100% Ether) MTBE (<=100% Ether) Used Oil	Mag Plus Probe for Alternative Fluids without Water Detection P/N 846391-4xx or -5xx	Inventory: Yes Leak Detection: Yes Water Detection: No	Alternative Fluids Float Kit P/N 846400-xy4* *Notes: x=0 -> 4" floats x=1 -> 2" floats x=3 -> 3" floats y=0 -> 5' cable y=1 -> 10' cable y=2 -> 20' cable
	Mag Plus Probe for Alternative Fluids without Water Detection P/N 846391-6xx	Inventory: Yes Leak Detection: No Water Detection: No	
Fuel Oil #4 & #6 Fuel Oil #4 & #6 Ethylene Glycol Propylene Glycol Windshield Washer Fluid	Mag Plus Probe for Alternative Fluids without Water Detection P/N 846391-6xx		

Leak Test Performance (Third Party Certified for all TLS-3xx Consoles*)

PROBE	TEST TYPE	P(D)	P(FA)	TEST TIME
0.1 GPH Mag Probe	0.1 GPH	99%	1%	3 Hours
0.1 GPH Mag Probe	0.2 GPH	99%	<.1%	2 Hours
0.1 GPH Mag Probe w/CSLD	0.2 GPH	99%	<.1%	Continuous
0.2 GPH Mag 2	0.2 GPH	99%	<.1%	2 Hours

Veeder-Root reserves the right to change product specifications without advance notice. Please ensure that you are using the latest version of product literature.



© 2007 Veeder-Root Company • 125 Powder Forest Drive • Simsbury, CT 06070 • USA
Telephone: 860-651-2700 • Fax : 860-651-2719 • www.veeder.com