



CONTAINMENT SOLUTIONS

August 1, 2011

Fuel Storage Compatibility

This letter applies to all fiberglass fuel storage products manufactured since the inception of Containment Solutions, Inc. (CSI) on 1/1/1995 including:

- Single-wall underground tanks
- Double-wall underground tanks
- Triple-wall underground tanks
- ReTank® (In situ double-wall tank upgrade)
- BTU® (Bio fuel Tank Upgrade for fluid compatibility)
- Single-wall tank sumps
- Double-wall tank sumps

CSI single, double, and triple wall tanks are listed by Underwriters Laboratories Inc., under UL Standard 1316 - *Glass-Fiber-Reinforced Plastic Underground Storage Tanks for Petroleum Products, Alcohols, and Alcohol-Gasoline Mixtures*.

All of the above Containment Solutions' products are compatible for use with the following fuels and fuel blends:

- Gasoline, jet fuel, aviation gasoline, motor oil (new or used), kerosene, diesel motor fuel
- Alcohol-gasoline blend motor fuels
 - Gasoline-ethanol blends with up to 100% ethanol
 - Gasoline-methanol blends with up to 100% methanol
- Biodiesel-diesel blends with up to 100% biodiesel (B100 per ASTM)
- Oxygenated motor fuels with up to 20% (by volume) methyl tertiary butyl ether (MTBE), ethyl tertiary butyl ether (ETBE), di-isopropyl ether (DIPE), tertiary butyl alcohol (TBA), tertiary amyl methyl ether (TAME), or tertiary amyl ethyl ether (TAEE)
- Diesel fuel oil

For more information on CSI products or CSI Field Services contact:

Containment Solutions

1-877-CSI-TANK

sales@csiproducts.com

www.containmentsolutions.com

Sincerely,

Ron Shaffer

Vice President Sales & Marketing

Containment Solutions, Inc.