

Gasoila Quick and Easy Sealant Reference Guide



Soft-Set

- General Purpose, Top-selling Sealant
- Perfect for New Pipes
- Stays Pliable in Cold Temperatures
- Non-Hardening,
- Non-Separating
- Non-Toxic

TYPE APPLICATIONS USED BY USED ON APPROVALS

Blue
Gray
Paste
with
PTFE

Water, Steam, Natural Gas, LPG, Propane, Gasoline, Butane
*Not for Use with Oxygen systems

- Mechanical Contractors
- Plumbers
- Gas Utilities
- Service Station Installers
- Manufacturing Plants

All Metals and Most Plastics

CSA, UL
NSF 61
NSF 14



E-Seal

- Specifically for E10 and E85
- Stays Pliable in Cold Temperatures
- Non-Hardening,
- Non-Separating
- Non-Toxic

Green
Paste
with
PTFE

Ethanol Blended Gasoline, including E10 and E85 (*NOT 100% Ethanol applications)
*Not for Use with Oxygen systems

- Gas Station Installers

All Metals

UL



Hard-Set

- Hard Setting Sealant
- Assembles Threaded Joints Permanently
- Excellent for Coating Surfaces.
- Impervious to Gasoline
- Flammable


Red
Varnish

Aliphatic, Aromatic and Chlorinated Solvents
*Not for Use with Oxygen systems

- Auto Industry to Seal Drive Trains, Coat parts
- Contractors Installing Underground Piping, Steam Systems
- Marine Manufacturers

All Metals, Rubber, Porcelain, Wood

UL



PLS-2

- Ideal for Demanding Pneumatic and LPG Applications


Gray
Paste
with
PTFE

Chlorine, Diesel, Jet Fuel, Steam, Dilute Acid, LPG
*Not for Use with Oxygen systems

- Chemical Plants,
- Gas Utilities
- Refineries
- Airlines, Hydraulics
- Tank Trucks

All Metals and Most Plastics

CSA
UL



100

- Ideal for use on Systems with 100% Methanol, Ethanol, Alcohol and Highly Corrosive Chemicals
- Soft Setting

Black
Paste


High Concentrations of Alcohol, Solvents, Caustic Chemicals
100% Ethanol
100% Methanol
*Not for Use with Oxygen systems

- Pharmaceutical
- Chemical Companies

All Metals and Fiberglass

*Not for Use on Plastic Pipe

*Threads must be Clean Prior to use



JC-30


- For Damaged, Irregular, Mis-cut and Straight Threads
- Vegetable Oil Base
- Thick Consistency, 10-15% more Solids than Conventional Sealants

Oyster
White
Paste
with
PTFE

Water, Steam, Natural Gas, LPG, Propane, Gasoline, Freon 22 and Hydraulic Fluids
*Not for Use with Oxygen systems

- Plumbers,
- Gas Utilities
- Manufacturing Plants

All Metals



NT

- Soft Setting for Applications Requiring Grit-Free, Non-PTFE Compound
- No Fillers to Contaminate Gas Lines
- For use when Non-PTFE Sealant is Preferred

Dark Blue
Paste
without
PTFE

Water, Steam, LPG, Propane, Gasoline
*Not for Use with Oxygen systems

- Propane Companies
- Petroleum Companies

All Metals and Most Plastics

NSF 61
NSF 14



FasSeal ATS

- Anaerobic Thread Sealant that cures in Absence of Oxygen
- Ideal for Refrigeration or other High Vibration Applications
- High Speed Curing Time
- Vibration Resistant

Smooth
White
Paste
with
PTFE

Air Conditioning Lines, Hydraulic-Pneumatic Lines, Air Compressor Hoses, Sprinkler Installations
*Not for Use with Oxygen systems

- HVAC
- Refrigeration Companies

Metals
*Not for Use on Plastic Pipe

UL

Phone: 800-846-7325 - Fax: 800-797-2080

#GCC4 JAN - 2015