

UL Product iQ™

MVQJ.MH14114 - Flammable Liquid and Diesel Exhaust Fluid
Hose Assemblies

Flammable Liquid and Diesel Exhaust Fluid Hose Assemblies

See General Information for Flammable Liquid and Diesel Exhaust Fluid Hose Assemblies

CONTITECH USA INC

703 S Cleveland Massillon Rd
Fairlawn, OH 44333-3023 USA

MH14114

Product Dsg	Nom Size, in.	Min Use Temp, °C	Fuel Rating	Additional Use Conditions
Flammable liquid hose assembly				
Fuelgrip 5/8, 3/4 and 1 in.	5/8, 3/4, 1	-40	Gasoline, Gasoline/ethanol blends up to E10	—
Chrome	5/8, 3/4, 1	-40	Gasoline, Gasoline/ethanol blends up to E10	—
"Flexsteel Futura"	5/8, 3/4, 1	-40	Gasoline, Gasoline/ethanol blends up to E10	—
"Flexsteel Futura E25"	5/8, 3/4	-40	Gasoline, Gasoline/ethanol blends up to E25	—
"Flexsteel Futura Ethan-All"	5/8, 3/4	-40	Gasoline, Gasoline/ethanol blends up to E85	—
"Flexsteel Futura B20"	3/4, 1	-40	Diesel/Biodiesel blends up to and including 20% Biodiesel	—
Futura "Low Perm"	3/4	-40	Gasoline, Gasoline/ethanol blends up to E10	Low Perm
Vapor recovery flammable liquid hose assemblies				
Futura "HVR Low Perm"	3/4	-40	Gasoline, Gasoline/ethanol blends up to E10	Low Perm
"Stage II", "SR1", "Premier LX", "Nozzle End Stage II",	1-1/4	-40	Gasoline, Gasoline/ethanol blends up to E10	—
"Flexsteel Vapor Assist", "Ambassador Vapor Assist", "Flexsteel Futura Vapor Assist", "Flexsteel Futura ORVR"	1-1/8 (3/4 in. hose), 1-1/4 (7/8 in. hose)	-40	Gasoline, Gasoline/ethanol blends up to E10	—

Trademark and/or Tradename: "PMR", **GOOD YEAR**, **VEYANCE** TECHNOLOGIES, **Continental****Continental** ContiTech