

Containment Sensors - Continued

SOLID-STATE NON-DISCRIMINATING DISPENSER PAN AND CONTAINMENT SUMP SENSORS

Note when ordering with TLS-350 Systems: Requires an Eight-Input Type A Sensor Interface Module (P/N 329956-001). Any combination of up to eight Solid-State Non-Discriminating Dispenser Pan and Containment Sump Sensors may be connected to one module.

Note when ordering with TLS-450 Systems: Requires a Sixteen-Input Universal Sensor/Probe Module (P/N 332812-001). Any combination of up to sixteen Solid-State Non-Discriminating Dispenser Pan and Containment Sump Sensors may be connected to one module.

Part No.	Item	List Price
794380-321	Solid-State Dispenser Pan Sensor*	
794380-351	Solid-State Containment Sump Sensor*	

***NOTE WHEN ORDERING:** Mounting brackets are required. You may order the Veeder-Root Universal Sensor Mounting Kit, Part No. 330020-012, see page 19.

SUMP SENSOR

Note when ordering with TLS-350 Systems: Requires an Eight-Input Interstitial/Liquid Sensor Interface Module (P/N 329358-001). Any combination of up to eight Series 7943 Interstitial Sensors for Fiberglass Tanks, Interstitial Sensors for Steel Tanks, Sump Sensors, Position Sensitive Pan/Sump Sensors or Hydrostatic Sensors may be connected to one module. Also compatible with TLS-300 Series (No additional module required).

Note when ordering with TLS-450 Systems: Requires a Sixteen-Input Universal Sensor/Probe Module (P/N 332812-001). Any combination of up to sixteen Sump Sensors may be connected to one module.

Part No.	Item	List Price
794380-208	Sump Sensor - 12 ft. cable	
794380-209	Sump Sensor - 30 ft. cable	

POSITION SENSITIVE PAN/SUMP SENSOR

Approved for monitoring high alcohol alternative fluids such as E85**.

Note when ordering with TLS-350 Systems: Requires an Eight-Input Interstitial/Liquid Sensor Interface Module (P/N 329358-001). Any combination of up to eight Series 7943 Interstitial Sensors for Fiberglass Tanks, Interstitial Sensors for Steel Tanks, Sump Sensors, Position Sensitive Pan/Sump Sensors or Hydrostatic Sensors may be connected to one module. Also compatible with TLS-300 Series (No additional module required).

Note when ordering with TLS-450 Systems: Requires a Sixteen-Input Universal Sensor/Probe Module (P/N 332812-001). Any combination of up to sixteen Position Sensitive Pan/Sump Sensors may be connected to one module.

Part No.	Item	List Price
794380-323	Position Sensitive Pan/Sump Sensor*** - 12 ft. cable	
331102-001	20' Replacement Cable - 2 Wire Sensors with Connector (Required if replacing a Sump Sensor (794380-209) that currently has a cable longer than 12')	

**Only sensors with serial number greater than 200,000 are compatible. If serial number is less than 200,000, replace cable with p/n 331102-001 (20ft) or 331102-002 (12ft, see Spare Parts page 6) and sensor will be high alcohol compatible.

***A core program has been established for the 794380-208/209 Sump Sensors that are being upgraded to the 794380-323 Position Sensitive Pan/Sump Sensor. A core credit of \$30.00 will be issued when the Sump Sensor is returned to Customer Service in Altoona, PA. An RGA number will be provided on the packing slip if the purchase order indicates upgrade to Position Sensitive Sensor. Otherwise, Customer Service can be contacted for an RGA.