

CORROSION CONTROL™ ADVANCED PROTECTION SUBMERSIBLE PUMPS

Available as a factory installed option on STPAG and IST biofuel compatible Submersible Turbine pPumps (STPs), Corrosion Control™ Advanced Protection defends STPs from accelerated corrosion.

TECHNICAL ADVANTAGES

- Powder-coated and E-coated finishes protect exterior cast surfaces from accelerated corrosion.
- Stainless steel fasteners, riser, variable length column pipe and coupler protect against corrosion and provide long service life.
- UL and cUL listed.

ORDERING INFORMATION

Advance Protection STPs shipped from the factory will list the combined part number. Complete part numbers have a specific order and are created using the following guidelines:

STP XXXXX Y-A-B

STP = Basic Model Designation (IST for variable speed models)

XXXXX = **Factory Installed Options** (Model designations may include one or more of the following characters in alphabetical order.)

AP = Corrosion Control™ Advanced Protection with coated exterior cast surfaces, stainless steel fasteners and piping, alcohol-gasoline compatible)

F = Floating suction adapter (1½" NPT female adapter)

H = High pressure deadhead output (150 and 200 models only)

K = Intake filter screen (IFS, factory installed to PMA)

M = MagShell™ (flow enhancing, expanded PMA shell)

R = Model R check valve (24 psi relief/22 psi reset for PLLD)*

W = Model W check valve (16 psi relief/13 psi reset for PPM4000)*

Y = Pump Motor Horsepower Rating

33 = 1/3 hp fixed speed 200 = 2 hp fixed speed

75 = 3/4 hp fixed speed VS2 = 2 hp variable speed**

150 = 1½ hp fixed speed VS4 = 4 hp variable speed***

A = Model Length

VL1 = Variable length range #1

VL2 = Variable length range #2

VL3 = Variable length range #3

B = Riser Pipe Length

Riser pipe length is expressed as two numeric characters that indicate the total length of the riser in inches. Riser pipes are available from 7" to 60" in 1" increments (additional charge for risers 31" or longer).

*If not otherwise specified, all STP models are supplied with standard model check valve (40 psi relief /35 psi reset for MLD, TS-LS300, and TS-LS500).

**Implied on IST models unless VS4 is specified.

*** IST models only.



Corrosion Control™ Advanced Protection STP shown with MLD+ and Intake Filter Screen (sold separately).

SYSTEM COMPONENTS

Add these Corrosion Control™ System items to your site to proactively prevent and detect corrosion.



**EVO™ 600 or
EVO™ 6000 ATG**



**WATER
SEPARATOR**



**MULTIPLEXING
SENSOR HUB**



**CORROSION
DETECTION SENSOR**



**DESICCANT
PACK**

ORDERING INFORMATION

Corrosion Control™ Advanced Protection Submersible Turbine Pumps Common Configurations

Model	Description	Model Length Range*
ISTAPMVS4-VL1	4 hp Corrosion Control™ AP variable speed with MagShell™	64"–92"
ISTAPMVS4-VL2	4 hp Corrosion Control™ AP variable speed with MagShell™	95"–156"
ISTAPMVS4-VL3	4 hp Corrosion Control™ AP variable speed with MagShell™	127"–218"
ISTAPM-1	2 hp Corrosion Control™ AP variable speed with MagShell™	59"–87"
ISTAPM-2	2 hp Corrosion Control™ AP variable speed with MagShell™	90"–151"
ISTAPM-3	2 hp Corrosion Control™ AP variable speed with MagShell™	122"–213"
STPAPM200-VL1	2 hp Corrosion Control™ AP fixed speed with MagShell™	63"–91"
STPAPM200-VL2	2 hp Corrosion Control™ AP fixed speed with MagShell™	94"–154"
STPAPM200-VL3	2 hp Corrosion Control™ AP fixed speed with MagShell™	126"–217"
STPAPHM200-VL1	2 hp Corrosion Control™ AP high pressure fixed speed with MagShell™	63"–92"
STPAPHM200-VL2	2 hp Corrosion Control™ AP high pressure fixed speed with MagShell™	94"–155"
STPAPHM200-VL3	2 hp Corrosion Control™ AP high pressure fixed speed with MagShell™	126"–218"
STPAP150-VL1	1½ hp Corrosion Control™ AP fixed speed	60"–88"
STPAP150-VL2	1½ hp Corrosion Control™ AP fixed speed	91"–152"
STPAP150-VL3	1½ hp Corrosion Control™ AP fixed speed	123"–214"
STPAPH150-VL1	1½ hp Corrosion Control™ AP high pressure fixed speed	61"–89"
STPAPH150-VL2	1½ hp Corrosion Control™ AP high pressure fixed speed	92"–152"
STPAPH150-VL3	1½ hp Corrosion Control™ AP high pressure fixed speed	124"–215"
STPAP75-VL1	¾ hp Corrosion Control™ AP fixed speed	57"–86"
STPAP75-VL2	¾ hp Corrosion Control™ AP fixed speed	88"–149"
STPAP75-VL3	¾ hp Corrosion Control™ AP fixed speed	120"–212"

Notes:

- Remove "M" from model number for non-MagShell™ pump motor assembly (where applicable).
- STPAP/ISTAP models are listed for compatibility with fuel mixtures containing diesel fuel with up to 20% biodiesel, 100% biodiesel, up to 85% ethanol with gasoline, and 20% MTBE, 20% ETBE or 17% TAME with gasoline.
- All models are supplied with a standard check valve unless factory option "R" or "W" is specified.
- All above ISTAP models can only be powered by a MagVFC™. 4 hp models require three-phase incoming power supply, 2 hp models can be supplied with single- or three-phase incoming power.
- All above STPAP models require single-phase, 208-230 VAC, 60 Hz incoming power.
- 4" riser pipe, if supplied locally, must be 4½" OD by 3/16" WT tubing.
- For riser pipe lengths 31" to 60", adder charge applies.

*Model length (A) defined as the dimension from the turbine manifold bottom to the pump motor inlet.

Factory Installed Options

Specified in model number at time of STP order.

Model	Description
F	Floating suction adapter, 1½" NPT female, must be factory installed
K	IFS (intake filter screen) factory assembled to pump motor assembly
R	Model R check valve, factory installed, for Veeder-Root™ PLLD Line Leak
W	Model W check valve, factory installed, for Red Jacket PPM4000 Line Leak

Field Installed Options

Model	Description
5874202800	MagVFC™, 2 hp or 4 hp variable frequency controller, one required per IST
400137908	Syphon check valve (when ordered with STP)
400818921	STP-CBS, single-phase control box with lockout switch, 110 Volt coil
402312931	STP-DHI + SPGC-220, combo DHI with factory wired SPGC-220 Guardian Series™ Single Phase Controller
402313921	STP-DHI-CBS, combo DHI with factory wired STP-CBS
402459931	Model 65 psi check valve (for slave of manifolded STPs with Veeder-Root™ PLLD)
402507930	Secondary syphon kit (when two syphon primes are required for one STP)
5800100220	SPGC-220 Guardian Series™ Single Phase Controller, 220 Volt
5800300100	STP-DHI, dispenser hook isolation for 110 Volt dispenser handle switches, up to eight each