



# XP FLEXIBLE PIPEWORK

APT™ XP pipework provides a highly flexible pipework solution that makes installation simple and easy in any weather condition or site configuration. XP pipework can be used in both pressure and suction applications, and is ideal for underground service station fuel delivery systems. The XP pipework system features controlled flexibility, even in low temperatures, permitting fast, easy installation.

| Reel Size               | Inches*      | cm*                   |
|-------------------------|--------------|-----------------------|
| Master                  | 91 x 33 x 74 | 231.1 x 83.8 x 187.9  |
| Super Master (S. Mast.) | 91 x 52 x 74 | 231.1 x 132.1 x 187.9 |

\*Reel dia. x width x hub dia.

## HIGHLIGHTS

- Available in 1", 1½", 1¾" and 2" diameters in a variety of coil lengths.
- The D-Series piping is a single wall, direct bury piping.
- The SC-Series piping provides additional environmental security as a secondary contained direct bury pipe.
- XP pipe features a 3 ft. bend radius for all pipe diameters making it one of the most flexible, yet durable fuel pipes available.
- No possibility of piping layer delamination due to the layered piping construction of high-grade material.
- With long coils (1000+ ft.) and simple fittings, XP pipework can be installed quickly without specialized tools in any weather.

## SPECIFICATIONS

- Primary layer construction of Nylon 12 - the fuel line material contains no polyethylene.
- Do not store piping in direct sunlight.

### Approvals/Certifications

- UL971 listed.
- Biofuel compatible (E85 and Biodiesel).

## ORDERING INFORMATION

| Model     | Description             | Ft.   | Reel      | Weight |  |
|-----------|-------------------------|-------|-----------|--------|--|
|           |                         |       |           | Lbs.   |  |
| XP-100-SC | 1" secondary contained  | 250   | Master    | 301    |  |
|           |                         | 500   | Master    | 408    |  |
|           |                         | 2500  | S. Master | 1299   |  |
| XP-100-D  | 1" single wall          | 250   | Master    | 258    |  |
|           |                         | 500   | Master    | 320    |  |
|           |                         | 100   | Master    | 250    |  |
| XP-150-SC | 1½" secondary contained | 250   | Master    | 333    |  |
|           |                         | 500   | Master    | 470    |  |
|           |                         | 1,000 | S. Master | 789    |  |
| XP-150-D  | 1½" single wall         | 1,500 | S. Master | 1061   |  |
|           |                         | 100   | Master    | 225    |  |
|           |                         | 250   | Master    | 270    |  |
| XP-175-SC | 1¾" secondary contained | 500   | Master    | 570    |  |
|           |                         | 1,000 | S. Master | 536    |  |
|           |                         | 1,500 | S. Master | 686    |  |
| XP-200-SC | 2" secondary contained  | 100   | Master    | 300    |  |
|           |                         | 250   | Master    | 405    |  |
|           |                         | 500   | Master    | 580    |  |
| XP-200-D  | 2" single wall          | 1,000 | S. Master | 1076   |  |
|           |                         | 250   | Master    | 552    |  |
|           |                         | 500   | S. Master | 914    |  |
| XP-200-D  | 2" single wall          | 250   | Master    | 427    |  |
|           |                         | 500   | S. Master | 664    |  |