

Dispensing Hose



	Approvals	Color	Hose ID	Gasoline	Diesel	B5	B20	E10	E25	E85	Other Media	Reinforcement
BC Cold Flex	UL 330 / CUL	●	3/4" and 1"	✓	✓	✓		✓				Textile
BC Gasoline	UL 330 / CUL	●●●●	5/8", 3/4" and 1"	✓	✓	✓		✓				Textile
BC Marina	UL 330 / CUL	●●	3/4" and 1"	✓	✓	✓		✓				Textile
DEF Dispensing		●	1/2", 3/4" and 1"								Ad Blue / DEF	Textile
Flexsteel Futura	UL 330 / CUL	●●●●●	5/8", 3/4" and 1"	✓	✓	✓		✓				Wire
Flexsteel Futura B20	UL 330B	●	3/4" and 1"	✓	✓	✓	✓	✓				Wire
Flexsteel Futura E25	UL 330A	●	3/4"	✓	✓	✓		✓	✓			Wire
Flexsteel Futura Ethan-ALL E85	UL 330A	●	3/4"	✓	✓	✓		✓	✓	✓		Wire
Flexsteel Futura HVR Low Perm	UL 330 / CARB / EVR	●	3/4"	✓				✓				Wire
Flexsteel Futura Low Perm	UL 330 Low Permeation Requirements	●	3/4"	✓	✓	✓		✓				Wire
Flexsteel Futura Vapor Assist	UL 330	●	3/4"	✓				✓				Wire
LPG Delivery Pro	UL 21	●	1/2", 3/4", 1", 1-1/4" and 1-1/2"								LPG and Natural Gas*	Textile
Maxxim Premier Ultra	UL 330 / CARB / EVR	●	1-1/4"	✓				✓				Wire
Pacer	UL 330 / CUL	●	5/8", 3/4" and 1"	✓	✓	✓		✓				Textile

*Only approved applications

FEATURE HOSE Patent Protected



Flexsteel® Futura™ Low Perm

The first UL Approved low permeation gasoline dispensing hose available to the market.

Flexsteel® Futura™ Low Perm dispensing hose offers superior, long-lasting service with multi-fuel capability. This hose is designed for use at filling stations to reduce permeation rates to 10 g/m²/day and improve air quality and emissions. Currently mandated for Ohio and New Jersey Stage II Vapor Assist decommissioning areas and for California conventional dispensing.

- Premium abuse-resistant cover compound with enhanced ozone resistance for service longevity
- Meets UL330 requirements
- Meets stringent permeation requirements of less than 10 grams/m²/day.

FEATURE HOSE



Flexsteel® Futura™ Ethan-ALL™

Only UL Approved E85 hose on the market.

Specifically designed, engineered and manufactured to meet stringent UL 330A standards for ethanol dispensing. These assemblies use the Continental proprietary Fuel Grip fitting with a premium nickel coating to ensure corrosion is limited.

- For both E25 and E85 dispensing
- Capable of handling all blends of ethanol E1 to E85