

Probe Description & Product Application	Mag Plus In-Tank Probe for Monitoring Light & Heavy Oil Products with & without Water Detection in both USTs and ASTs					
Specific Products Monitored / Product Compatibility	Part # & Description	Approved Products (Use with Light Oil Float Kit)	Monitoring Functionality Options			
	<u>No Leak Detection/Inventory Only Probes with Water Detection</u> 1. 0846397-3xx Stainless Steel (SS) In-Tank Probe with High Grade Polymer (HGP) Canister with Water Detection & No Leak Detection/Inventory Only, UL <u>No Leak Detection/Inventory Only Probes with No Water Detection</u> 1. 0846397-6xx SS In-Tank Probe with HGP Canister with No Water Detection & No Leak Detection/Inventory Only, UL	Bio Diesel (High Density – Specific Gravity > 0.865) *	No Leak Detection / Inventory Only			
		Fuel Oil #4				
		Motor Oil **				
		Gear Oil, 90W				
		Toluene				
		Transmission Fluid				
Console Compatibility	Maximum Probes / Console	Probe Interface Modules				
		Module Part #	Module Description	# of Modules per Console	# of Probe Inputs per Module	Availability
TLS-450PLUS (8600 Series) with TLS-XB installed (3 max per system)	64	0332812-001	Universal Sensor Module (USM) Interface for Probes, Sensors, and DPLLD	Up to 4	16	Sold Separately (either Factory Installed or as a Spare Module)
TLS4 (8601 Series)	12	No module required, probe input capability factory installed				
TLS4B (8601 Series)	6					
TLS-350/R/PLUS	16	0329356-002	4-Input Probe Interface Module	4	4	Sold Separately (either Factory Installed or as a Spare Module)
TLS-300i	4	No module required, probe input capability factory installed				
TLS-300C	2					
Float Installation Kits	Part # & Description	Float Size	Cable Lengths	Min/Max Probe Length		
	0846400-0x4 Mag Plus Alternative Fluids Float Kit – No Water Float	4" (10.16cm)	5' (1.5m), 10' (3.05m)	48" (1.2m) - 144" (3.66m)		
	0846400-1x4 Mag Plus Alternative Fluids Float Kit – No Water Float	2" (5.08cm)				
	0846400-002 Light Oil	4" (10.16cm)				
	0846400-102 Light Oil	2" (5.08cm)				
	0846400-007 Heavy Oil	4" (10.16cm)				
	0846400-107 Heavy Oil	2" (5.08cm)				

* Tank testing approved for: B6-B20 meeting ASTM D7467 and B100 meeting ASTM D6751

** Compatible with tank testing