



FIBERGLASS COMPOSITE PIPE DIVISION
1004 Ameron Road.
Burkburnett Texas, 76354

May 19, 2008

Hector P. Mercado
Engineering Manager
940-569-8607
Fax: 940-569-8644
hmercado@ameronfpd.com

Ref: Fuel Compatibility of Dualoy® 3000/L & 3000/LCX

Ameron's Dualoy® 3000/L & 3000/LCX piping systems have been tested and were found to comply with the applicable requirements of UL971, Standard for Nonmetallic Underground Piping for Flammable Liquids with revisions through and including March 2, 2006. These include:

Diameters 2", 3", 4" & 6" Series Dualoy 3000/L Primary Carrier and Secondary Containment Piping, Diameters 2", 3" & 4" Series Dualoy 3000/LCX Integral Primary/Secondary Piping and Series PSX-20 and PSX-34 adhesives for conveying Primary Product, Vent and Vapor Recovery of Motor Vehicle Fuels, Concentrated Fuels, High Blend Fuels and Aviation and Marine Fuels.

Based on all available testing Ameron finds the following fuels suitable for use with the Dualoy® 3000/L and 3000/LCX piping systems: B2, B20, B100, E10, E85, E100, low/medium/high grades of unleaded, aviation and marine fuels.

The primary pipe for the Series Dualoy® 3000/L system has maintained the same design performance since 1988.

Sincerely,

A handwritten signature in blue ink that reads 'Hector Mercado'.

Hector Mercado
Engineering Manager