

<b>Sensor Description</b>	<b>Position Sensitive Sensor</b>	This sensor is installed in a containment sump or dispenser pan and will detect the presence of, and differentiate between, hydrocarbons and other liquids.				
<b>Part Number</b>	794380-323					
<b>Category</b>	<input type="checkbox"/> Discriminating <input checked="" type="checkbox"/> Non-Discriminating <input checked="" type="checkbox"/> Position Sensitive		<input type="checkbox"/> Level Sensing <input type="checkbox"/> Static Testing <input type="checkbox"/> Hydrostatic			
<b>Fuel Compatibility</b>	<input checked="" type="checkbox"/> Gas <input checked="" type="checkbox"/> Diesel <input checked="" type="checkbox"/> Kerosene <input checked="" type="checkbox"/> Jet Fuel <input checked="" type="checkbox"/> Aviation Gas		<input checked="" type="checkbox"/> E-15 <input checked="" type="checkbox"/> E-85 <input checked="" type="checkbox"/> E-100 <input checked="" type="checkbox"/> Bio-Diesel 20 <input type="checkbox"/> Bio-Diesel 100			
<b>Console Compatibility (*International Only<sup>1</sup>)</b>	<b>Recommended Min. Console Software</b>	<b>Sensor Interface Modules</b>				
		<b>Module Part #</b>	<b>Module Description</b>	<b># of Modules per Console</b>	<b># of Sensor Inputs per Module</b>	<b>Availability</b>
TLS-450PLUS (8600 Series)	6A or Higher	332812-001	Universal Sensor Module (USM)	Up to 4 - TLS-4XX Up to 8 - TLS-4XX w/ opt. TLS-XB	16	Sold Separately
TLS-450	4A or Higher					
TLS4 (8601 Series) <sup>1</sup>	6A or Higher	330020-750	Universal Sensor Input Output Module (USIOM-AC)	1	12	Included
TLS4i (8601 Series)						
TLS4B (8601 Series) <sup>1</sup>						
TLS4c (8601 Series)						
TLS-350/R/PLUS	124/324 or Higher	329358-001	Interstitial Sensor Interface Module	Up to 8	8	Sold Separately
TLS-350J		329356-003	4 Probe / 4 Sensor Interface Module	1	4	Sold Separately
TLS-300i		330230-001	4 Probe / 8 Sensor Interface Module		8	Included
TLS-300C		330513-001	2 Probe / 8 Sensor Options			
<b>Alarm Notification</b>	Normal	Sensor in Normal State - No liquid detected				
	Sensor Out	Sensor not resting on bottom of containment or sensor not communicating to ATG/Console				
	Fuel Alarm	Liquid detected in containment area at approx. 1.5" (3.81cm)				
<b>Installation Kit</b>	330020-012	Universal Sensor Mounting Kit (Sold separately)				
<b>Specifications</b>	<b>Example Installation</b>					
Operating Principle	Product Permeable, Reed Switch / Float					
Product Activation Height	Liquid - Approx. 1.5" (3.81cm)					
Operating Temperature	+32 to +140°F (0 to +60°C)					
Dimensions	12" (30.5cm) high, 2.2" (5.6cm) dia.					
Miscellaneous/Notes	Standard Cable Length: 12ft (3.66m).					
Third Party Evaluation Links	<a href="#">TLS-3XX/TLS-450 Series Consoles</a> <a href="#">TLS4 (8601 Series) Consoles</a>					
Product Link	<a href="#">Position Sensitive Sensor</a>					
Warranty with System	1 Yr Parts & Labor					
Warranty (When purchased separately)	1 Yr Parts Only					
<b>Where Used (Typical)</b>	<input checked="" type="checkbox"/> Dispenser Pan <input checked="" type="checkbox"/> Spill Containment <input checked="" type="checkbox"/> STP Sump <input type="checkbox"/> Convault Tank <input type="checkbox"/> Annular Space <input type="checkbox"/> Monitoring Well <input type="checkbox"/> Oil/Water Separator Tank					