

UL Product iQ™



EUCV.MH9253 - Shutoff Valves, Emergency

Shutoff Valves, Emergency

[See General Information for Shutoff Valves, Emergency.](#)

FRANKLIN FUELING SYSTEMS INC

MH9253

3760 MARSH RD

MADISON, WI 53718-6900 USA

Emergency shutoff valves for flammable liquids, Model 662 with upper adapter Nos. 662-F, -FP, 662-M, -MP, 662-U, -UP.**Vapor line shear valves**, Models 362-200, 362-204, may be followed by -01, -02, -03, -04.

Model 362-206, may be followed by 13 or 31.

Trademark and/or Tradename: "EBW"

[Last Updated](#) on 2019-11-26

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"



EUCV.GuideInfo - Shutoff Valves, Emergency

[Dispensing Devices] (Dispensing-device Accessories) Shutoff Valves, Emergency

See [General Information for Dispensing-device Accessories](#)

USE

This category covers emergency shutoff valves and vapor line shear valves intended for use with power-operated dispensing devices handling flammable liquids (other than LP-gas) and diesel exhaust fluid (DEF). Emergency shutoff valves incorporate a thermal element and are designed to close automatically in the event of breakoff resulting from severe impact or fire exposure. Refer to the individual certifications for the specific liquids for which these valves have been investigated.

This equipment is intended for use with fuels formulated in accordance with 40CFR80, "Regulation of Fuels and Fuel Additives," and the following:

- a) gasoline formulated in accordance with ASTM D4814, "Standard Specification for Automotive Spark-Ignition Engine Fuel"
- b) gasoline/ethanol blends at levels designated as "gasohol" (E10) or less formulated in accordance with ASTM D4814, when blended with denatured fuel ethanol formulated in accordance with ASTM D4806, "Standard Specification for Denatured Fuel Ethanol for Blending with Gasolines for Use as Automotive Spark-Ignition Engine Fuel"
- c) gasoline/ethanol blends at levels designated greater than 10% ethanol (E10) formulated in accordance with ASTM D5798, "Standard Specification for Fuel Ethanol (Ed75-Ed85) for Automotive Spark-Ignition Engines"
- d) diesel fuel formulated in accordance with ASTM D975, "Standard Specification for Diesel Fuel Oils"
- e) kerosene formulated in accordance with ASTM D3699, "Standard Specification for Kerosine"
- f) fuel oil (heating fuel) formulated in accordance with ASTM D396, "Standard Specification for Fuel Oils"

Unless otherwise specified in the individual certifications, suitability of use with biofuels has not been determined.

PRODUCT IDENTITY

One of the following product identities appears on the product:

- Emergency Shutoff Valve for DEF
- Emergency Shutoff Valve for Flammable Liquids
- Vapor Line Shear Valve

ADDITIONAL INFORMATION

For additional information, see [Dispensing Devices \(EPWR\)](#) and [Flammable and Combustible Liquids and Gases Equipment \(AAPQ\)](#).

REQUIREMENTS

The basic standard used to investigate products in this category is one of the following:

[UL/ULC 842](#), "Valves for Flammable and Combustible Liquids" — For products intended for use with gasoline or gasoline/ethanol blends with nominal ethanol concentrations up to 10 percent (gasohol, E10), diesel fuel, diesel/biodiesel blends with nominal biodiesel concentrations up to 5 percent (B5), kerosene, fuel oil, LP-gas, manufactured gas, or natural gas.

[UL 842A](#), "Valves for Gasoline and Gasoline/Ethanol Blends with Nominal Ethanol Concentrations up to 85 Percent (E0 - E85)" — For products intended for use with gasoline or gasoline/ethanol blends with nominal ethanol concentrations up to 85 percent (E85).

[UL 842B](#), "Valves for Diesel Fuel, Biodiesel Fuel, Diesel/Biodiesel Blends with Nominal Biodiesel Concentrations up to 20 Percent (B20), Kerosene, and Fuel Oil" — For products intended for use with diesel fuel, biodiesel fuel, diesel/biodiesel blends with nominal biodiesel concentrations up to 20 percent (B20), kerosene or fuel oil.

[UL 87C](#), "Outline of Investigation for Power-Operated Dispensing Devices for Diesel Exhaust Fluid," and [UL/ULC 842](#) — For products intended for use with diesel exhaust fluid.

UL MARK

The Certification Mark of UL on the product or on the smallest unit container in which the product is packaged is the only method provided by UL to identify products manufactured under its Certification and Follow-Up Service. The Certification Mark for these products includes the UL symbol, the words "CERTIFIED" and "SAFETY," the geographic identifier(s), and a file number.

Alternate UL Mark

The Listing Mark of UL on the product or on the smallest unit container in which the product is packaged is the only method provided by UL to identify products manufactured under its Listing and Follow-Up Service. The Listing Mark for these products includes the UL symbol (as illustrated in the Introduction of this Directory) together with the word "LISTED," a control number, and the product name "Emergency Shutoff Valve for DEF," "Emergency Shut-Off Valve for Flammable Liquids" or "Vapor Line Shear Valve."

If the Listing Mark is cast or molded into the product, the product identity may be omitted. However, the complete Listing Mark, including the product identity, will also be provided on the smallest unit container in which the product is packaged.

* * * * *

UL, in performing its functions in accordance with its objectives, does not assume or undertake to discharge any responsibility of the manufacturer or any other party. UL shall not incur any obligation or liability for any loss, expense or damages, including incidental or consequential damages, arising out of or in connection with the use, interpretation of, or reliance upon this Guide Information.

Last Updated on 2020-08-26

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"